


Overview and trends of the different emitter type for LIDAR

Mergl | 03.12.2019 | DVN – conference (Frankfurt)

Light is OSRAM

OS is a long-time partner for lasers in the automotive industry

First use of LiDAR since early 2000s




905 nm pulse Laser,
75 W, 20 ns

More than 10 car OEMs
use laser based AEB¹
systems with
OSRAM's 905nm laser
already today

OS with pioneer role and a proven track record

- > 10 year of LiDAR Laser supplier to automotive industry
- > 10 million LiDAR lasers in the field without *chip failures*
- > 200 Billion km

The Future of Autonomous Driving




Correlation technology ⇔ application is exemplary only


Value propositions of different technologies (selection)

- Camera** Color vision and ability to recognise signs
- Radar** Speed detection / darkness
- LiDAR** 3D capability; high angular resolution / darkness

Two basic LiDAR technologies




- The whole FOV is illuminated at once using a wide-angle beam
- No moving parts in the LiDAR module



- Scanning, narrow emitter beam which is being moved across the FOV over time
- Mechanical solution or micro-mirrors used for beam steering

Comparing - Near Infrared IR-A (905nm) vs Near Infrared IR-B (1550nm)

905nm will stay dominant LIDAR wavelength in the market due to superior emitter and detector performance



Key Parameter	EEL 905nm	EEL 1550nm	Fiber 1550nm
Laser technology	InGaAs/GaAs	InP / InGaAsP	980nm or 1480nm Pumping / Erbium doped Fiber
Peak Power	+	0	++
Beam quality	+	+	++
Compactness	++	+	0
Operating Temperature range	++	+	0
Cost	++	+	0
Water absorption [cm ⁻¹]	+	0	0
Eye safety	+	++	++

Key Parameter	Sensor 905nm	Sensor 1550nm
Detector Technology	Si	InGaAs
Operation Temp. Range	++	+
Detector Noise	++	0
Cost	++	0
Integration of electronics	++	0

0 poor
 + good
 ++ very good

Emitter comparison

Edge Emitting Laser vs. Vertical cavity surface emitting Laser

EEL dominate for long range scanning LIDAR due to high power density. VCSEL good alternative for Flash LIDAR




Parameter	EEL	VCSEL
Laser technology	InGaAs/GaAs	InGaAs/GaAs
Wavelength	905nm	850nm, 940nm
Emitting structure	Edge emitting	Surface emitting
Spectral width	± 3 nm	± 3 nm
Optical Power	Scales with Length	Scales with Area
Power density (emitted area)	~ 60 kW /mm ²	~ 120 W/mm ²
Slope efficacy	~ 3 W/A	~ 1 W/A
Radiation Characteristic	Elliptical	Gaussian
	e.g. $\pm (7^\circ \times 25^\circ)$ design	e.g. $\pm 20^\circ$ (design)
Wavelength shift vs. Tj	0.3 nm/K	0.07 nm/K
Temperature Range	-40°C ... 105°C	-40°C ... 105°C
Rise- and Fall time	< 1 ns	< 1 ns


Sunspectrum and required detection bandwidth

The bigger Wavelength shift of the EEL905 has lower system influence as expected

Only Laser temperature shift considered



System Detection Bandwidth² (temperature, WL binning..)




- Temperature Range of -40°C to 105°C
- Depending on bandwidth we integrate over a given wavelength range of the ASTM reference spectrum -> NOISE

LIDAR Technologies

Different LiDAR systems may require different light sources

High Power VCSEL is under evaluation at OSRAM OS



Short Range

0 m – 40 m
City Traffic,
Autobahn lane change

Mid Range

1 m – 90 m
City Traffic,
Country Road crossing
Autobahn rear view

Long Range

1 m – 200 m (250m)
Autobahn, long distance view

Flash LiDAR



MEMs LiDAR




Mechanical Scanning LiDAR



Portfolio Development: EEL for LiDAR

Today

Future



In Mass Production today ...

... and Future concepts

Portfolio Investment

VCSEL

Today

Future



Consumer

Automotive interior

LIDAR

BIDOS
PLPVQ 940A



0.6 W

BIDOS
PLPVCQ 850
PLPVCQ 940



2 W

BIDOS
PLPVEC2 850
PLPVDC2 940



3-4 W

BIDOS
PLPVCQ 940A_P
PLPVCQ 940B_P



2 W

BIDOS
Automotive



4W
FOV (h x v) 120° x 90°

BIDOS
Automotive




3 W
FOV (h x v) 47° x 35°

**VCSEL array concepts
For LIDAR**



Multichip arrays,
Multichannel



Single chip solutions

What comes next

- In Production

- Samples available 2020
- Automotive release Q4 2020

Thank you.