

System design considerations for a short-range segmented flash LiDAR

DVN LiDAR Conference 2023 in Wiesbaden



29-30
NOV.
2023
FRANKFURT

DVN
Lidar

**6TH DVN AUTOMOTIVE
LIDAR CONFERENCE
& EXPO**

"2024 - The Year Lidar Breaks out!"

DORINT HOTEL PALLAS WIESBADEN, FRANKFURT AREA

Clemens Hofmann, Senior Principal Engineer LiDAR, ams-OSRAM International GmbH
2023-11-30

Short Range LiDAR use cases in Automotive Applications

Market trend seen for short range LiDAR sensors using flash VCSEL technology

Short range LiDAR use cases



Urban pilot (UP)



Parking




L4/L5 Robo Taxi (RT)

Market forecast short range LiDAR – Yole report

- ADAS
 - slow penetration as OEMs focus on TJP and HWP
 - applied in urban L2 use cases (mainly in China)
 - parking is appearing
- Robo trucks and Robo taxis
 - require SR for L4 functionality
 - slow growth compared to ADAS


AM LiDAR, # of SR sensors in millions



Short Range LiDAR use cases in Automotive Applications

Market trend seen for short range LiDAR sensors using flash VCSEL technology

LiDAR Sensor with segmented flash technology




Segmented Flash

- light up only one segment (e.g., a line) of the VCSEL
- read out matching SPAD segment
- light up next segment of VCSEL
- read out next segment of SPAD

VCSEL and SPAD segments need to match

Optical distortions in the far field



Optical distortions



- image of VCSEL segment can be distorted, especially toward outer edge of FoV

Distortions of optics for emitter and detector need to be matched

Segmented Flash LiDAR concepts

Identical pixel pitch for TX and RX ease optical design but are challenge for VCSEL design

VCSEL



SPAD





photo: Sony homepage



Key take aways

Optics


- Same pitch for VCSEL and SPAD
- TX and RX can use same optics
 - identical distortions

VCSEL design (e.g., for IMX459)

- 56 rows x 192 apertures (30µm pitch)
- large VCSEL, low fill factor
- challenging for VCSEL design rules

Driver


- What about multi-channel driver



Segmented Flash LiDAR concepts

Identical pixel pitch for TX and RX ease optical design but are challenge for VCSEL design and driver design

Capacitor Voltage Control – 1D VCSEL



Key take aways

VCSEL specifications

- Target is $>100\text{W}$ per line
- 20-30A needed per line
- 500-1000nJ pulse energy



Driver

- $30\mu\text{m}$ channel pitch will be challenging for multi-channel driver

Segmented Flash LiDAR concepts

Different pixel pitch for TX and RX ease VCSEL design and driver design but make optics more complicated

VCSEL



SPAD





photo: Sony homepage



Key take aways

Optics


- Different pitch for VCSEL and SPAD
- TX and RX use different optics
 - challenge to match distortions

VCSEL design 100W (e.g., for IMX459)

- 56 rows x 192 apertures (50µm pitch)
- Well within VCSEL design rules
- Very large VCSEL, low fill factor

Driver

- feasible for multi-channel driver




Segmented Flash LiDAR concepts

1:1 pixel relationship eases optics design at cost of large VCSEL. Homogeneous line allows small VCSEL, but optics design is challenging

1:1 pixel relationship

VCSEL design for 100W


- 56 rows x 192 small apertures
- Well within VCSEL design rules
- Very large VCSEL, low fill factor



Homogeneous line illumination

VCSEL design for 100W

- 56 rows x 40 large apertures
- Well within VCSEL design rules
- Large VCSEL, good fill factor



Key take aways

1:1 pixel relationship

- 1:1 aspect ratio requires large VCSEL
- Simple optics can be used, although it is more challenging for different pitch sizes of VCSEL and SPAD

Homogeneous line illumination


- Illuminations of SPAD row with homogeneous line leads to smaller VCSEL
- Optics will be more complicated

Automotive VCSEL Product Roadmap at ams-OSRAM

Addressable VCSEL feature enables segmented flash

AM VCSEL Product Portfolio

1D-addressable VCSEL – Segmented Flash



1:1 pixel relationship

Oslo 905 & 940nm
80 x 100W

5


Homogeneous line

Riga 905nm
56 x 250W

8

Riga 940nm
56 x 250W

8



1D-addressable VCSEL – OSLO Evaluation kit


- Motherboard + Tx Board with VCSEL + VCSEL driver
- Available with 905nm or 940nm Tx VCSEL Board
- Software and firmware elements included for operation

Tx Board

- Oslo VCSEL → 72 x 30W peak optical power
- 2 Driver ICs
- Mechanical interface for optics

Motherboard

- Signal and power I/F to Tx Module
- FPGA and Raspberry Boards
- Power management



Summary

Close alignment needed between Optics, SPAD, VCSEL, and Driver companies to enable optimal sensor system

Key take aways

Pixel Pitch of TX and RX


- **Identical pitch:** easy for optics, challenge for VCSEL and Driver
- **Different pitch:** easy for VCSEL and driver, more complex optics

Optics Concept

- **1:1 pixel relationship:** simple optics, large VCSEL
- **Homogeneous line:** small VCSEL, challenging optics

Road to Success

- Close alignment and exchange between optics, SPAD, VCSEL, and driver suppliers to enable optimal sensor system



Sensing is life

am  OSRAM